



Car number --- _____

Technical Inspection (Autocross Only)

Tech team _____

DRIVERS MUST OPEN THEIR CARS, TECHS NOT TO OPEN HOOD, DOORS OR TRUNKS

Interior

- ___ Seats and seat belts and components must be securely fastened
- ___ Seat Belts or harnesses required, minimum of 2-point, safe and operational
- ___ Convertibles require minimum 3-point seat belts and proper roll over protection
- ___ Steering "spinner" knobs are prohibited
- ___ All loose items must be removed from the vehicle, including trunk
- ___ Pedal operation must not be impeded; drivers floor mat must be removed
- ___ Brake pedal must hold pressure, no hydraulic leaks or fade
- ___ Any fluid lines passing through the driver compartment must be metal braided or similar, excluding oil pressure gauge

Exterior

- ___ Vehicle height must not exceed track width (track width is measured from the center of tire on one side to the center of the other side tire)
- ___ Snap on hubcaps, trim rings, detachable fender skirts must be removed
- ___ All lug studs and nuts must be present and functional
- ___ Tires must have no cords or belts showing at the start of competition
- ___ Wheels must not have cracks or potentially dangerous damage
- ___ Wheel Bearings, shocks, steering and suspension components must be in good operating condition with no free play
- ___ Gas cap securely fastened
- ___ Brakes must be adequate condition with sufficient fluid in the master cylinder
- ___ Battery hold down required
- ___ Throttle return action shall be safe
- ___ No *excessive* leaks.